

[New 300-365 Dumps Braindump2go 300-365 VCE Dumps and 300-365 PDF Dumps 122Q Download][83-93

2018/September Braindump2go 300-365 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-365

Real Exam Questions: 1. | 2018 Latest 300-365 Exam Dumps (PDF & VCE) 122Q&As

Download: <https://www.braindump2go.com/300-365.html> | 2018 Latest 300-365 Exam Questions & Answers

Download: <https://drive.google.com/drive/folders/0B75b5xYLjSSNZTJ3Y0Z5b0NFRFE?usp=sharing> QUESTION 83A wireless printer has been configured with a static IP address. Which action does the Cisco WLC take in response? A. It does not transfer AAA requests to the printers. B. It does not transfer ARP requests to the printers. C. It does not transfer join requests to the printers. D. It does not transfer location information to the printers. Answer: B Explanation:

<https://www.cisco.com/c/en/us/support/docs/wireless/wireless-lan-controller-software/118833-wlcdesign-ftrs-faq.html>

QUESTION 84 Which option is a physical entity in converged access wireless network design? A. mobility domain B. switch peer group C. mobility group D. mobility agent Answer: C QUESTION 85 A sporting arena has a new wireless network and finds that clients are not connecting to their nearest access point. Which setting can be enabled to minimize this behavior and reduce the AP view of channel utilization? A. Use an RF profile with an RX-SOP threshold. B. Enable Band Select C. Enable Client Balancing D. Turn on CleanAir Answer: A QUESTION 86 Which option is a calibration of a Cisco MSE deployment limited to when that deployment is using the linear point collection method? A. rogue AP B. associated 802.11 a/n clients C. RFID tag D. associated 802.11 b/g/n clients Answer: A Explanation:

https://www.cisco.com/c/en/us/td/docs/wireless/mse/8-0/MSE_CMX/8_0_MSE_CAS/7_4_MSE_CAS_chapter_01010.html

QUESTION 87 When CAPWAP protocol runs over IPv4, which UDP port numbers are used for control and data traffic, respectively? A. control 5246, data ?UDP-Lite(IP Protocol 136) B. control 5247, data ?5246 C. control 5246, data ?5247 D. control 5247, data ?UDP-Lite(IP Protocol 136) Answer: C QUESTION 88 An engineer has deployed a WLAN in a high-density auditorium and expects the number of clients to grow. Which WLC configuration can be used to increase the IP space without any service disruptions? A. dynamic interface B. interface group C. AP group D. RF group Answer: B QUESTION 89 A security engineer wants all guest users to be terminated on the DMZ of their firewall. Which two configurations must be implemented to fulfill this new requirement? (Choose two.) A. TCP port 16666 and 16113 in an ACL on the controller B. UDP ports 16666 and IP protocol 97 on the firewall C. a mobility group with a controller in an isolated network on the firewall D. an RF group with a controller in an isolated network on the firewall E. UDP ports 1812 and 1645 in an ACL on the controller Answer: B C QUESTION 90 Which two access categories could use TXOP value higher than 0, as per 802.11e standard? (Choose two.) A. AC_VO B. AC_BK C. AC_VI D. AC_BE Answer: A C Explanation:

<https://www.cisco.com/en/US/docs/solutions/Enterprise/Mobility/emob30dg/WANQoS.pdf> QUESTION 91 A wireless engineer is configuring a Cisco MSE by using the automatic installation script. Which two parameters are mandatory and must be configured at least once? (Choose two.) A. Ethernet interface B. hostname C. GRUB password D. domain name E. NTP server Answer: A B Explanation: Please note that the following parameters (indicated by *) are mandatory and must be configured at least once. -> Hostname -> Network interface eth0 -> Timezone -> Root password -> NCS Communication username -> NCS Communication password https://www.cisco.com/c/en/us/td/docs/wireless/mse/7-6/Virtual_appliance/Installation_Config_Guide/Cisco_MSE_VA_Config_Guide/Installing_MSE_Virtual_Appliance.html QUESTION 92 Clients on

access points within an AP group are not receiving multicast traffic after roaming to another AP within the AP group. Which configuration must be done to maintain multicast connectivity? A. Enable an ACL on the router that serves the VLAN or subnet. B. Enable NAC out-of-band support. C. Enable a unique NAS-ID for the AP group. D. Enable IGMP snooping. Answer: D

Explanation: <https://www.cisco.com/c/en/us/support/docs/wireless-mobility/wireless-lan-wlan/81671-multicastwlc-lap.html>

QUESTION 93 Which two parameters are used by MSE location analytics to determine the behavior of a Wi-Fi device? (Choose two.) A. the transmit power B. the Wi-Fi channel C. the dwell time D. the path choice E. Layer 2 roaming Answer: C D

Explanation: https://www.cisco.com/c/en/us/td/docs/wireless/mse/3350/7-4/Location_Analytics_Service/Guide/Cisco_Location_Analytics_Service_Configuration_Guide/Location_analytics_overview.html !!!RECOMMEND!!!

1. | 2018 Latest 300-365 Exam Dumps (PDF & VCE) 122Q&As Download: <https://www.braindump2go.com/300-365.html> | 2018 Latest 300-365 Study Guide Video: YouTube Video: [YouTube.com/watch?v=dX3mpZXC43g](https://www.youtube.com/watch?v=dX3mpZXC43g)